

Nuova Distribution USA, LLC

6940 Salashan Parkway, Building A • Ferndale, WA 98248 www.nuovadistribution.com • (p) 360-366-2226 • (f) 360-366-4015

Theresia 220v Spec Sheet

Water Requirements

- 3/8" dedicated cold water line with shut-off valve and compression fitting. (optional)
- Water hardness cannot exceed 3gpg or 50 ppm. If water hardness exceeds 3gpg a water softener must be installed.
- Minimum incoming water flow rate of 35 GPH and maximum line pressure of 70 PSI / 5 BAR.

Water Softening Equipment

- 1. Water Softener Capacity: Single 4400 gpg
- 2. Water Softener Capacity: Double 8800 gpg
- 3. Water Softener Capacity: Triple 13200 gpg
- 4. Water Softener Capacity: Automatic Programmable
- 5. Water Softener Capacity: Manual 4400 gpg

Power Requirements

• Volts: 220 (voltage range of 208-240)

Watts: 3000Amp draw: 15

Receptacle: Nema 6-20









NSF / ANSI Std.4

The average water consumption of this machine is 2 gallons per day, which represents 64 drinks at 4oz per drink.

Water Softener/Maintenance Calculation

Cartridge Grain Capacity Gallons of Water Hardness (grains per gallon) = Gallon Capacity Gallons of Water Used per Day = Days Until Cartridge Needs to be Replaced

Shipping Dimensions & Weight

Height: 26 inchesDepth: 36 inchesWidth: 30 inchesWeight: 110 pounds


Counter Space Requirements

Height: 22 inchesDepth: 21 inchesWidth: 16 inchesWeight: 82 pounds

Drain Requirements (optional)

 Open gravity drain of minimum 1.25 inch I.D., within 4 feet of the machine. (optional)

Countertop Drain Hole Location





I, the customer, understand that these requirements must be in when the installer arrives. Failure to have the site re	eady
will result in additional service and travel charges, and may cause further delays in installation.	

Will recent in additional convict and traver charges, and may eace farmer delays in inclanation.			
Customer Name:	Signature:		
Company Name:			
Phone:	Fax:	Email:	